

PRE-OILED TIMBER DECKING & CLADDING


THE FUTURE OF TIMBER PROTECTION.

WHAT IS 'PRE-OILED' TIMBER?

Pre-oiling is the process of applying one-coat of Intergrain Universal Timber Oil to your timber.

To fully protect your pre-oiled timber, **apply a top coat within 12 weeks of installation.**

THE PRE-OILED ADVANTAGE



360° PROTECTION

- Pre-oiling protects all sides.
- Better protection during transport, site storage and installation.



DEEPLY PENETRATING

- Protects the structural integrity of the timber.
- Reduces warping, cupping or splitting.
- Minimised moisture absorption.



UNLOCKED TECHNOLOGY

- Compatible with most water or oil based finishes.
- Alternatively leave pre-oiled to naturally grey-off.



SAVES TIME

- No need to weather the timber, simply clean and coat.
- Less prep, no sanding. Saves time on-site.
- Less dependence on weather conditions.

AUS_TIM
SUSTAINABLE TIMBER SOLUTIONS

Intergrain

TRADE & INDUSTRIAL

TOP COATING OPTIONS

LONG LASTING PROTECTION FOR PRE-OILED TIMBER

LEAVE TO NATURALLY GREY-OFF

Your pre-oiled timber is protected with Intergrain® Universal Timber Oil. If you are looking to allow a natural greyed-off look then top coating is not required. The pre-oiled timber whilst initially appearing dark will gradually be dulled by UV exposure.

TIP During timber installation, touch up any cut-ends with your chosen finish to help maintain 360° protection.



TOP COATING

STEP 1: Clean

Ensure surface is clean. If required, clean with Intergrain® UltraPrep™ Timber Cleaner.

Intergrain® UltraPrep Timber Cleaner

- High strength.
- Concentrate, water soluble.
- Environmental friendly.



STEP 2: Coat

Once dry, apply 2 coats of your chosen water or oil based finish, following the label instructions.

Intergrain® UltraDeck Timber Stain or Timber Oil

- Water based.
- Lasts 3x longer *than traditional decking oils.



OR

Intergrain® Universal Timber Oil

- Clear finish.
- Highlights the natural look of timber.
- Colour additives available.



TIP Always test your chosen coating and colour in a small inconspicuous area first.

CARE & MAINTENANCE LONG LASTING PERFORMANCE

Best protection of the timber and ease of longer term maintenance is ensured if the timber finish is recoated before any deterioration of the coating and timber underneath. Conduct regular cleaning removing any surface contamination. Inspect every 6 – 12 months, looking for any signs of deterioration such as patchiness, discolouration or poor water repellence on the surface or edges of the timber. We recommend a clean, repair and touch up of any minor damage when it is first observed.

Austim, Perth WA
Call (08) 6558 1266
austim.com.au

AUS-TIM
SUSTAINABLE TIMBER SOLUTIONS

Intergrain Trade & Industrial
Call 1800 630 285
intergrain.com.au/industrial

Intergrain.
TRADE & INDUSTRIAL